

OLDROYD'P' PlasterMembrane



Cover damp, contaminated walls instantly. Then apply a plaster finish.

Description

Oldroyd 'P' is a studded polypropylene waterproofing membrane with a special mesh welded to one side. It is fixed to damp, contaminated walls using Oldroyd Plaster Plugs, with the studs facing the wall. This creates an air-gap, which allows the wall to breathe whilst blocking the passage of moisture.

On the reverse side of the membrane, the special mesh can be plastered onto, allowing a dry plaster finish to be achieved without risk of contamination from any damp or salts in the wall.

Oldroyd 'P' can also be used on external walls to provide protection against penetrating damp.

Oldroyd 'P' can be used above or below ground, however we recommend that our technical department is consulted before using the product below ground.



Advantages

Oldroyd 'P' Plaster Membrane is especially useful in situations where a damp wall is contaminated by salts or the residue of previous attempts to waterproof the wall (such as bitumen). Unlike cementitious waterproofing products, Oldroyd-P Plaster Membrane can be applied directly to contaminated surfaces with minimal preparation.



Technical information



OLDROYD'P' PlasterMembrane



Application

Oldroyd 'P' is hung vertically on the wall, and is fixed into place using specially designed Oldroyd Plaster Plugs.

Joints are sealed using Oldroyd Sealing Tape. A

plaster finish* is then applied in accordance with good practice.

Detailed application instructions are available on request, or can be downloaded from

www.safeguardchem.com.

Dry Lining

As an alternative to a plaster finish, plaster board can be applied directly to Oldroyd 'P' Plaster membrane.

The plasterboard is attached to the membrane by

applying dabs of bonding compound to the heads of the Oldroyd Plaster Plugs that are used to attach the membrane to the wall.

Consideration should also be made to the use of

Oldroyd Xv membrane, which can be used in

conjunction with dry lining, and requires fewer fixings.



Availability

Oldroyd 'P' Plaster Membrane is available in 2m x 20m rolls (40m²).

NEW Plaster Membrane Kit

A complete kit is now available containing everything you need to cover 7.5m²:

1.5 x 5m roll of Oldroyd P plaster membrane

100 plaster plugs with seal

6m roll of sealing tape

Disclaimer:

The general information provided in the present technical description, application guidelines and other recommendations, is based on research and experience. However the client is obliged to determine himself what products are suitable for use. Accordingly, no liability will be accepted by IBC.

For further information contact the IBC Technical Department.



Technical information

IBC Limited, Unit 143, Grange Drive, Baldoyle Industrial Estate, Baldoyle, Dublin 13
Tel: +353 1 8321005 Fax: +353 1 8393539 Email: info@ibcltd.net www.ibcltd.net